

弯道加宽工程数量表

S3-6-2

西林县足别瑶族苗族乡平木村央报屯至那朋油茶产业基地道路硬化工程

序号	起止柱号	加宽位置	加宽总长度	加宽宽度	加宽总面积	18cm水泥混凝土面层	10厘米厚碎石垫层	加宽缓和段		加宽标准段		加宽缓和段		备注
								缓和段长度	数量	标准段长度	数量	缓和段长度	数量	
			(m)	(m)	(m ²)	(m ²)	(m ²)	(m)	(m ²)	(m)	(m ²)	(m)	(m ²)	
1	K1+227-K0+255	内侧	28	2.0	46.0	46.0	46.0	5.0	5.0	18.0	36.0	5.0	5.0	
2	K1+312-K0+340	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
3	K1+398-K1+426	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
4	K1+718-K1+746	内侧	28	2.0	46.0	46.0	46.0	5.0	5.0	18.0	36.0	5.0	5.0	
5	K1+971-K1+999	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
6	K2+418-K2+446	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
7	K2+492-K2+520	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
8	K2+652-K2+680	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
9	K2+720-K2+748	内侧	28	2.0	41.0	41.0	41.0	5.0	2.5	18.0	36.0	5.0	2.5	
合 计					379.0	379.0	379.0							